

TECHNICAL DATA SHEET

ATF DX-3

DESCRIPTION

ATF DX-3 is a high quality multi-vehicle automatic transmission fluid designed for use where DX-3, DX-2, Mercon®, Mercon® V, JASO M315 Type 1A, Chrysler ATF+4, Nissan Matic D, Toyota T-IV and other high viscosity automatic transmission fluids are specified. It is also commonly used as a power steering fluid and hydraulic oil in jacks and hoists. ATF DX-3 meets the most demanding high viscosity ATF specifications with a robust, shear stable formulation offer enhanced viscosity control and anti-shudder protection throughout the drain interval.

SUMMARY OF BENEFITS

- Approved for a wide range of automatic and hydraulic transmissions
- May be used for service fill or top up where the listed fluid specifications are recommended
- Provides excellent protection of mobile hydraulic pumps such as those of Denison, Sperry Vickers and Sundstrand
- Greatly improved low temperature properties for smooth cold shifts
- Excellent shear stability for long fluid and component life
- Has unsurpassed retention of frictional coefficient, for consistently smooth gear changes

SUITABLE FOR



SPECIFICATIONS

- DX-3, DX-2
- ALLISON C4
- CATERPILLAR TO-2
- CHRYSLER ATF+4
- MERCON®, MERCON® V
- JASO M315 TYPE 1A
- NISSAN MATIC D
- TOYOTA T-IV

SUITABLE FOR

- FORD/BTR 85LE AND 95LE
- POWER STEERING SYSTEMS CALLING FOR DX-3
- MANY HYDRAULIC APPLICATIONS CALLING FOR ISO 32 TO ISO 46

ATF DX-3	TEST METHOD	UNITS	RESULTS
DENSITY @ 15°C	ASTM D1298	kg/L	0.854
KINEMATIC VISCOSITY @ 40°C	ASTM D445	cSt	38.5
@ 100°C	ASTM D445	cSt	7.5
VISCOSITY INDEX	ASTM D2270	-	164
POUR POINT	ASTM D97	°C	-42
FLASH POINT (COC)	ASTM D92	°C	193
APPEARANCE	-	-	RED

Typical characteristics are only a guide to industry and are not necessarily manufacturing or marketing specifications and do not constitute any legal liability.

STORAGE INSTRUCTIONS & HEALTH, SAFETY AND ENVIRONMENT INFORMATION

All packages should be stored under cover to avoid the possible ingress of water and the obliteration of drum markings. Products should not be stored above 60°C. Health, safety and environmental information is provided for this product in the relevant Materials Safety Data Sheet, which can be obtained by contacting Gulf Western Oil on: 02 9673 9600.

AVAILABLE PACK SIZES

IBC - #30041B, 205LT - #30041, 60LT - #36041, 20LT - #32041, 4LT - #30441, 1LT - #30141

October 2024