

DESCRIPTION

Agriblue is a synthetic high performance UTTF - Universal Tractor Transmission Fluid - suited to tractors requiring a common oil for transmissions, hydraulics, differentials, final drives, wet clutches, and brakes. The anti-squawk additive ensures effective operation of wet brakes. This highly boosted formulation was developed for high horsepower tractors operating in severe applications.

SUMMARY OF BENEFITS

- Significantly increased gear wear protection
- Correct frictional characteristics ensure quiet wet brake operation
- Proven field performance
- Good anti-foam characteristics
- Based on borate technology
- Excellent shear stability performance is maintained, and very high thermal/oxidation stability provide long fluid life
- Good water tolerance ensures hydraulic performance is maintained and very high thermal/oxidation stability providing long fluid life

SUITABLE FOR



SPECIFICATIONS

- API GL-4
- SAE 10W-30 (TABLE J300)
- SAE 80 GEAR OIL (TABLE J306)
- JOHN DEERE J20C. J20D
- NEW HOLLAND FORD (New Holland Group)
- MASSEY FERGUSON
- CASE CORP (JI Case & International Harvester)
- KUBOTA
- WHITE FARM
- AGCO
- ALLISON
- ZF

AGRIBLUE	TEST METHOD	UNITS	RESULTS
DENSITY @ 15°C	ASTM D7042	kg/L	0.863
KINEMATIC VISCOSITY			
@ 40°C	ASTM D7042	cSt	67.3
@ 100°C	ASTM D7042	cSt	10
@ 100°C	CEC L-45-A-99	cSt	8.25
VISCOSITY INDEX	ASTM D2270	-	132
POUR POINT	ASTM D97	°C	-36
FLASH POINT (COC)	ASTM D92	°C	210

Typical characteristics are only a guide to industry and are not necessarily manufacturing or marketing specifications and do not constitute any legal liability.

STORAGE INSTRUCTIONS & HEALTH, SAFETY AND ENVIRONMENT INFORMATION

All packages should be stored under cover to avoid the possible ingress of water and the obliteration of drum markings. Products should not be stored above 60°C. Health, safety and environmental information is provided for this product in the relevant Materials Safety Data Sheet, which can be obtained by contacting Gulf Western Oil on: 02 9673 9600.

AVAILABLE PACK SIZES

IBC - #30048B, 205LT - #30048, 20LT - #32048