

TECHNICAL DATA SHEET

SYN-TS™ ATF



DESCRIPTION

SYN-TS™ ATF is a fully synthetic ATF multi functional transmission fluid that is formulated to meet the requirements of most modern and older automatic transmissions. Suitable for extended drain intervals up to 150,000 km's for general use and 80,000km's for heavy duty applications. It covers a wide range of specifications making it a true multi functional product.

SUMMARY OF BENEFITS

- SYN-TS™ is suitable for use in ZF 6 Speed ZF6HP26 Transmissions
- Eliminates the requirement to stock additional fluids
- Suitable for older, modern and high performance applications
- Formulated with Enhanced frictions modifiers and high VI
- Can be used where a DX-6, DX-3, V1, Ford 95LE, Nissan J Matic Range, ATF +4, Mitsubishi SPII, SPIII and Allison C4 fluid is called for
- Excellent low temperature viscometrics
- GL-4 equivalent gear protection
- Decreased down time and greatly reduced wear
- Extended drain intervals and excellent shear stability
- Minimal viscosity loss
- Reduced oxidation
- Superior frictional properties and softer gear change
- Improved sludge and varnish control

SUITABLE FOR



SPECIFICATIONS

- AISIN WARNER AW1 236.2, 236.5, 236.6,
- ALLISON C4 236.7, 236.9, 236.10,
- ALLISON TES - 295 236.11, 236.14
- AUDI G 052 162 • MITSUBISHI SPII, SPIII
- AUDI G 052 990 • NISSAN Matic D, J, K, S
- AUDI G 052 025 • NISSAN 402
- BMW 7045E • SHELL 3403, LA2634
- BMW LA 2634 • SUBARU ATF, ATF-HP
- BMW LT 71141 • TEXACO ETL 7045E
- CHRYSLER ATF, MOPAR AS68RC • TEXACO ETL 8072B
- DX-3 • TOYOTA T-III, T-IV, WS
- DX-6 • (JWS 3324)
- ESSO LT 71141 • VOITH 55.6335.XX
- FORD TYPE FNRS, 85LE/95LE • (G607)
- FORD MERCON V • VOITH 55.6336.XX
- HONDA ATF Z1 • (G1363)
- HYUNDAI SP II, SP III, SPH-IV • VOLVO PASSENGER CAR
- HYUNDAI NWS-9638 • (4 - 6 SP)
- IDEMITSU K17 • VOLVO 97340, 97341
- JASO 1-A • VW 052 162
- JWS 3309, 3324 • VW 052 990
- KIA SP II, SP III • VW 055 025
- MAN 339F, V1, V2, Z1, Z2 • ZF TE-ML 03D, 04D,
- MAZDA ATF M III, MV 05L, 09X, 11B, 14A, 14B,
- MERCEDES 236.1, 16L, 17C, 20B

SYN-TS ATF 10W	TEST METHOD	UNITS	RESULTS
DENSITY @ 15°C	ASTM D1298	kg/L	0.850
KINEMATIC VISCOSITY			
@ 40°C	ASTM D445	cSt	36
@ 100°C	ASTM D445	cSt	7.0
VISCOSITY INDEX	ASTM D2270	-	158
POUR POINT	ASTM D97	°C	-42
FLASH POINT (COC)	ASTM D92	°C	224

Typical characteristics are only a guide to industry and are not necessarily manufacturing or marketing specifications and do not constitute any legal liability.

STORAGE INSTRUCTIONS & HEALTH, SAFETY AND ENVIRONMENT INFORMATION

All packages should be stored under cover to avoid the possible ingress of water and the obliteration of drum markings. Products should not be stored above 60°C. Health, safety and environmental information is provided for this product in the relevant Materials Safety Data Sheet, which can be obtained by contacting Gulf Western Oil on: 02 9673 9600.

AVAILABLE PACK SIZES

IBC - #30058B, 205LT - #30058, 60LT - #36058, 20LT - #32058, 4LT - #30458

October 2024

GULF WESTERN PREMIUM QUALITY LUBRICATING OILS (AUST) PTY LTD

Head Office: 92-96 Links Road, St Marys NSW 2760 - PO BOX 515 Kingswood, NSW 2747
 Phone: 02 9673 9600 - Fax: 02 9623 6466 - Email: sales@gulfwestern.com.au - Web: www.gulfwestern.com.au