

TECHNICAL DATA SHEET

DOT 4 BRAKE FLUID

DESCRIPTION

A high performance brake fluid suitable for both passenger and commercial vehicles including ABS systems. Has high temperature resistance and low moisture absorption providing superior boiling point and high vapour lock temperature throughout its service life.

Please note: Dot 4 Brake Fluid is compatible with Dot 3 Brake Fluid.

DIRECTIONS FOR USE

1. Clean and flush system prior to refilling
2. Add fluid in accordance to vehicle manufacturer's recommendation
3. Reseal container immediately after to avoid contamination and absorption of moisture

IMPORTANT NOTE:

- Do not allow contact with paintwork
- Do not mix brake fluids
- Dispose of empty containers properly. Do not use empty container for storing other fluids



SPECIFICATIONS

- AUSTRALIAN STANDARD - AS/NZS 2960.1-2005 (DOT 4)
- SAE J1704
- SAE J1703
- ISO 4925
- FMVSS 116

DOT 4 BRAKE FLUID	
APPEARANCE	Green Liquid (also available in clear by request)
ODOUR	Slight Odour
PH	7.0 to 8.0
FLAMMABLE	Class C1 Combustible
MELTING POINT	N/A
BOILING POINT	N/A
SOLUBILITY	Soluble
FLASH POINT	>130°C
RESERVE ALKALINITY	40.00

Typical characteristics are only a guide to industry and are not necessarily manufacturing or marketing specifications and do not constitute any legal liability.

STORAGE INSTRUCTIONS & HEALTH, SAFETY AND ENVIRONMENT INFORMATION

All packages should be stored under cover to avoid the possible ingress of water and the obliteration of drum markings. Products should not be stored above 60°C. Health, safety and environmental information is provided for this product in the relevant Materials Safety Data Sheet, which can be obtained by contacting Gulf Western Oil on: 02 9673 9600.

AVAILABLE PACK SIZES

IBC - #40001B, 205LT - #40001, 20LT - #42001, 5LT - #40501, 500ML - #40101

October 2024